



POSBANK®

APEXA®G POS Terminal

Connect It to All + Install It Anywhere + Save Time and Cost

APEXA®G is POSBANK's latest POS terminal which reinterprets the traditional forms of mechanical looking in a modern and contemporary style. Its unrivaled innovative design enables customers to enjoy space efficiency and usability at the same time.

 Supermarkets

 Apparels

 Mobile Shops

 Pharmacies

 Hardware

 Grocery Shop

Top Features



- Low-Power High-Performance Intel® Celeron® J1900 Quad-Core Processor
- Compact and Sleek. Small Footprint
- 15" Bezel-Free True-Flat PCAP Touch
- Display with LED Backlight
- Multiple I/O Interfaces for Peripherals
- Flexible Deployment on a Counter or a Wall
- Modern and Contemporary Styling for Interior Decor
- Fast Installation and Easy Serviceability
- Engineered and Optimized for Hospitality and Retail Businesses



Specifications

System

Processors

Intel® Celeron® J1900 (2M Cache, 2.0/2.42 GHz (Burst), 4Cores), Fanless

Chipset

Intel® Bay Trail

Memory

4/8GB RAM

Storage

SSD 64/128GB

Operating Systems

No OS or Windows 10

Audio

Realtek ALC662-VD

Display

Type

15" TFT LCD, LED Backlight

Resolution

1024 x 768

Brightness

800 cd/m2 (typ.)

Touchscreen

Projective Capacitive Touch

Interface

Display

1 x VGA (With Power Output)

USB

- 6 (Rear 2, Back 4, USB 2.0 x 6)
- 3 (Reserved for MSR, SCR, i-Button /Touch Controller/Camera), RJ-45

- 6 (COM 1 with 5V/12V Power Output on 9 Pins, BIOS)

- (COM2-3 RJ-45, Full Signal)

Serial

(COM4 RJ-11, Only TX/RX, 12V Power Output, Reserved for CDP) (COM5 Reserved for Cash Drawer Port)

(COM6 RJ-45, Only TX/RX, 5V Power Output, Reserved for MSR)

LAN

1 x Gigabit Ethernet, RJ-45

Audio

1x Line-out

Power DC-IN

1 x (4 Pin Connector)

Power Supply

Adaptor 12V, 5A

Optional Peripherals



2nd Display
9.7" LCD



Customer Display
VFO (2 Line x 20 Characters)



Card Reader
MSR and FIMS